



Pilkington **Activ™** Neutral Self-cleaning Solar Control Glass



The attractive neutral coloured glass that combines dual-action, self-cleaning properties with solar control performance for a cooler internal environment.

Specially designed for conservatories and large glazed areas, Pilkington **Activ™** Neutral is a revolutionary new glass that is perfect for use in both the roof and verticals. It uses daylight and rainwater to breakdown and wash away organic dirt from exterior surfaces, making it ideal for hard to clean areas and giving you a year-round clearer view of your garden when used in conservatory verticals. Its unique solar control coating also helps keep internal temperatures cool whilst still maintaining excellent, neutral light transmittance. For optimum self-cleaning and thermal performance, combine Pilkington **Activ™** Neutral with Pilkington **K Glass™** or Pilkington **Optitherm™** SN in an insulating glass unit.



PILKINGTON

A member of NSG Group

New Pilkington **Activ™** Neutral

	Light		Solar Energy				Shading Coefficient			U value (W/m²K)	
	Transmittance	Reflectance (external)	Direct Transmittance	Reflectance	Absorptance	Total Transmittance	Short Wavelength	Long Wavelength	Total	Air	Argon
Insulating glass unit with 16mm cavity and 4mm Pilkington Activ™ Neutral outer pane											
4mm Pilkington Optifloat™ Clear inner pane	0.45	0.30	0.40	0.24	0.36	0.47	0.46	0.08	0.54	2.7	2.6
4mm Pilkington K Glass™ inner pane	0.42	0.31	0.35	0.24	0.41	0.43	0.40	0.09	0.49	1.7	1.5
4mm Pilkington Optitherm™ SN inner pane	0.44	0.29	0.30	0.28	0.42	0.38	0.34	0.10	0.44	1.4	1.2

Argon gas filled IGU's based on 90% gas fill determined in accordance with EN410 and EN673.



Pilkington **Activ™** Neutral must always be processed, installed and maintained in accordance with our specialist Handling and Processing instructions.

Benefits

- Neutral appearance offers attractive aesthetics and optimum performance
- Excellent solar control performance combined with good light transmission
- Uses daylight and rainwater to breakdown dirt and wash away organic dirt from the exterior of the glass
- Works even on cloudy days and during the night
- Pilkington **Activ™** coating lasts the lifetime of the glass
- Easily cleaned during dry spells by hosing down
- Neutral appearance in transmission and reflection makes Pilkington **Activ™** Neutral ideal for use in both the walls and roofs of conservatories
- Easily stocked and fabricated into Insulating Glass Units in annealed and toughened forms, ensuring speedy delivery
- Available in 4mm thickness
- Can be combined with Low E glass (Pilkington **K Glass™** or Pilkington **Optitherm™** SN) and argon gas for the ultimate in conservatory glazing



CE marking confirms that a product complies with its relevant harmonised European Norm.
The CE marking label for each product, including declared values, can be found at www.pilkington.com/CE



PILKINGTON

Building Products - UK

Prescot Road St Helens WA10 3TT United Kingdom
Telephone 01744 692000 Fax 01744 692880
pilkington@respond.uk.com
www.pilkington.com/selfcleaningglass