

Product Identification	Thermally toughened soda-lime silicate safety glass (e.g., 4–19 mm thickness).
Intended Use	Glass for use in buildings and construction works in accordance with the harmonised standard.
Manufacturer	Express Toughening Ltd 51-55 Fowler Road, Hainault Business Park, Ilford, Essex, IG6 3XE 020 8500 1188 www.expresstoughening.com
Authorised Representative	Not applicable
System of Assessment and Verification of Constancy of Performance (AVCP)	System 3
Harmonised Standard	BSEN 12150-2

Safety Classification	Essential Characteristics	Declared Performance
Safety In The Case of Fire	Reaction to fire (EN 13501-2)	NPD
	Reaction to fire (EN 13501-1)	A1
	External Fire Performance (EN 13501-5)	NPD
Safety In Issue	Bullet Resistance (EN 1063)	NPD
	Explosion Resistance (EN13541)	NPD
	Burglar Resistance (EN356)	NPD
	Pendular Body Impact Resistance (EN12600)	1C1
Thermal Properties	Normal Emissivity Coated Side	NPD
	U-Value (w/m ² k)	NPD
Radiation Properties	Light Transmission	NPD
	Light Reflection	NPD

The performance of the product identified above is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer

Name: Adam Curtis

Position: Director

Current Version date of Issue: 16th March 2026

Signature:



EXPRESS TOUGHENING LIMITED

 020 8500 1188

 info@egw.co.uk

 020 8500 1010

 www.egw.co.uk

 51-55 Fowler Road, Hainault Business Park, Ilford, Essex, IG6 3UT

FOLLOW US ON SOCIAL MEDIA

